



Description

The standard meshes we offer to our customers have an opening which may range between 25 microns and 30 mm.

Reti Service is a service for the reconditioning of mesh support rings of any kind, with any type of mesh and drilled sheet, even for vibrating screens not manufactured by us. Maximum celerity and quality at competitive prices.

Applications

- Circular vibrating screen
- Direct discharge screen with one side motor
- Direct discharge screen with two side motors
- Direct discharge screen with central motor
- Tumbling screen
- Trommel

MESHES

Technical data sheet



Mesh	French number	NT	No. of links per sq cm	Wire Ø mm	Useful surface %	Net opening mm
33,56	3,89	7	1,96	1	73,8	6,14
4,57	5	9	3,24	1,1	64,2	4,45
5,08	5,56	10	4	1	64	4
7,11	7,78	14	7,84	0,8	60,1	2,77
8,63	9,45	17	11,56	0,6	63,3	2,34
10,16	11,1	20	16	0,8	46,2	1,7
10,67	11,68	21	17,64	0,9	38,6	1,48
11,68	12,79	23	21,16	0,9	34,7	1,28
12,7	13,89	25	25	0,7	42,2	1,3
13,71	15,01	27	29,16	0,65	42	1,2
15,24	16,68	30	36	0,7	33,9	0,97
17,78	19,46	35	49	0,5	42,4	0,93
22,85	25	45	81	0,4	40,8	0,71
28	30,55	55	121	0,32	42,1	0,59
35,6	38,92	70	196	0,3	33,7	0,415
45,72	50	90	324	0,2	41,1	0,356
50,8	55,56	100	400	0,15	49	0,35
60,96	66,67	120	576	0,18	32,1	0,236
71,1	77,78	140	784	0,16	30,4	0,197
81,25	88,9	160	1024	0,12	37,7	0,191
101,6	111,11	200	1600	0,1	36	0,15
121,8	133,3	240	2304	0,09	32,1	0,118
147,32	161	290	3364	0,07	35	0,102
162,45	177,73	320	4096	0,06	37,7	0,096
182,74	200	360	5184	0,05	41,1	0,089
208,2	222,22	400	6400	0,05	36	0,075
228,4	250	450	8100	0,05	30,1	0,061
253,82	277,77	500	10000	0,04	36	0,06
274,11	300	540	11664	0,04	32,8	0,053
325	355	640	16384	0,035	30,3	0,043
350	383	690	19044	0,035	26,8	0,037
406,21	444,44	800	25600	0,03	27	0,032
450	500	900	32400	0,028	45	0,027
500	556,6	1000	40000	0,025	25	0,025